DC Φ175x69mm - A

General Specifications

Material:……Frame:Aluminium
Impeller: ……Impeller:PA66 Plastic(UL94V0)
Expected Life: ……Ball Bearing 50,000hrs (40℃)
Motor Control Method.....FOC Three-Phase Motor
IP Class Protection.....IP44; installation- and position-dependent
Lead Wire: ……+red -black or yellow Signal,blue Speed control
Temperature Range: ……Operating temperature -10℃～60℃(Humiditumidity 35%~85%RH)
Storagetemperature -30℃～70℃(Humiditumidity 35%~85%RH)
Signal output: ……FG Signal / RD Signal (Open Collector Output)
Speed control mode: ……Vsp:0~10 V ~ 10V PWM Control
Net Weight: ……1.5Kg

External Dimension



Air Flow - Static Pressure Characteristics



MODEL	Rated Voltage (V)	Operating Voltage Range (V)	Rated Current (Amp)	Rated Input Power (W)	Rated Speed (rpm)	Air Flow		Static Pressure		Sound level dB(A)
						(CFM)	m^3/min	(mmH2O)	inch-H2O	
CB17569H24X	24	12~25.6	2.90	69.60	3500	317.33	8.986	58.65	2.434	72.5
CB17569H48X	48	36~54	1.35	64.80	3300	295.06	8.262	40.86	1.601	70.3

Specifications are subject to change without notice

NIKCOOL

DONGGUAN YIJIN ELECTRONIC CO.,LTD