DC 120x120x25mm - E

General Specifications

Material:.....Frame:Plastic(UL94V0)
Impeller: .....Impeller:Plastic(UL94V0)
Expected Life: .....FDB Bearing 60,000hrs (40℃)
Ball Bearing 50,000hrs (40℃)
Long Life Bearing 25,000hrs (40℃)
Lead Wire: .....+red -black or yellow Signal,blue Speed control
Temperature Range: .....Operating temperature -10℃～70℃(Humiditumidity 35%~85%RH)
Storagetemperature -30℃～70℃(Humiditumidity 35%~85%RH)
Signal output: .....FG Signal /RD Signal
Speed control mode: .....PWM Control

Dimensions



Air Flow - Static Pressure Characteristics



MODEL	Rated Voltage (V)	Operating Voltage Range (V)	Rated Current (Amp)	Rated Input Power (W)	Rated Speed (rpm)	Air Flow		Static Pressure		Sound level dB(A)
						(CFM)	m^3/min	(mmH2O)	inch-H2O	
CD12025L12X	12	7~13.8	0.33	3.96	2000	54.49	1.526	2.26	0.089	35.0
CD12025M12X		7~13.8	0.45	5.40	2500	67.52	1.891	3.28	0.129	41.5
CD12025H12X		7~13.8	0.58	6.96	3000	84.28	2.360	4.75	0.187	47.5
CD12025L24X	24	12~25.6	0.14	3.36	2000	54.49	1.526	2.26	0.089	35.0
CD12025M24X		12~25.6	0.20	4.80	2500	67.52	1.891	3.28	0.129	41.5
CD12025H24X		12~25.6	0.28	6.72	3000	84.28	2.360	4.75	0.187	47.5

Specifications are subject to change without notice